

# P820 Smoothing Kit



**A820-XX-N-SSM**

## Ordering Information:

# A820-XX-N-SSM

### SMOOTHING KITS

A820-XX-N-SSM	Standard Smoothing kit Manifold mounted for 5-30:1 Ratios
A820-40-N-SSM	Standard Smoothing kit Manifold mounted for 40:1 Ratio
A820-XX-N-NSM-*	Non-Standard Smoothing kit Manifold mounted for 5-30:1 Ratios
A820-40-N-NSM-*	Non-Standard Smoothing kit Manifold mounted for 40:1 Ratio

\*Nitrogen precharge in accumulator must be specified.

## Applications:



**Pressure Sustaining**



**Intermittent Operations**

## Description

- Significantly reduces pressure pulsations created from hydraulic pumps.
- Maintains a volume of pressurized fluid to absorb system shocks.
- Maximum pulsation dampening occurs when installed as close to the outlet port as possible.

HYDRONIC WARRANTY POLICY: Hydronic, Corp. warrants each product against defects in material and workmanship for a period of 6 months from the date of manufacturing providing its use was in accordance with Hydronic recommendations. If the product fails to perform as warranted, Hydronic will, at its option, repair or replace the product free of charge. The company will not be liable for incidental or consequential damages. We make no other warranty, expressed or implied, including warranties of merchant ability or fitness for a particular purpose.